

Eckel® 7⁵/₈ HDS-25

Casing Tong 2³/₈ - 7⁵/₈ in.

Maximum Torque 25,000 ft-lbs (33895 Nm)



When applications demand a wide range of sizes, this tong handles pipe sizes 2³/₈ to 7⁵/₈ inches. The 7⁵/₈ HDS-25 uses a two-speed mechanical shift transmission in conjunction with the two-speed Hydra-Shift® motor, providing the operator a very flexible choice of working torque/RPMs during makeup or breakout. Our **patented CASE STIFFENER** technology enhances overall torque to provide consistent torque output. Having a high full 360° rotational torque and speed-shifting capability ensures the tong can makeup special torque-turn connections that require continuous rotation. Also, the CASE STIFFENER technology reduces stress and wear on the rotary gear teeth.

Our CHROMEBOSS® series of tongs are suitable for running corrosion-resistant alloy (CRA) tubular. Two slide heads in the tong provide a constant radial load on the tubular, reduced tubular deformation, and when combined with our pyramid fine-tooth or True-Grit™ wrap-around dies, provides excellent gripping capabilities on corrosion-resistant alloy (CRA).

Features

- Maximum Torque:
25,000 ft-lbs (33895 Nm)
- CASE STIFFENER Technology Enhanced
- Flexible Choice of Torque & RPM with Hydra-Shift® Motor and Two Speed Gear Train, (4) Torque Levels / (4) RPM Speeds
- Self Aligning Throat
- Drop-in Style Bracket/Mount Shaft Encoder
- Chain Bridle or Solid Hanger
- Wrap-Around Dies or Rig Dies: Steel Fine Tooth / Coarse Tooth, **True Grit®** Non-Marking dies

Options

- Tri-Grip® Backup: Compression or Tension
- RPM Control
- Torque Turn Control System
- In-line Electronic Dump Valve
- Open/Close Center Convertible Control Valve
- Door Interlock
- Lift Cylinder
- Spring Hanger



TONG SPECIFICATIONS

Capacity	2 ³ / ₈ - 7 ⁵ / ₈ in. (60.3 - 193.7 mm)
Dimensions	30 x 60 in. (762.0 x 1524.0 mm)
Weight ^[1]	1,500 lb. (680.4 kg)
Maximum Torque @ 2500 PSI (172 bar)	
High-High	4,350 ft-lb (5898 Nm)
High-Low	8,550 ft-lb (11592 Nm)
Low-High	12,825 ft-lb (17388 Nm)
Low-Low	25,000 ft-lb (33895 Nm)
Maximum RPM @ 65 GPM (246 LPM)	
High-High	125
High-Low	64
Low-High	23
Low-Low	11
Handle Length	36.5 in. (927.1 mm)
Certifications	CE or DNV Optional

BACKUP SPECIFICATIONS

Backup Type	Tri-Grip Backup
Capacity	2 ³ / ₈ - 9 ⁵ / ₈ in. (60.5 - 244.5 mm)
Dimensions ^[2]	38.5 x 60 in. (927.1 x 1524.0 mm)
Weight ^[1] ^[2]	2,850 lb. (1293 kg)
Load Cell Type	Compression or Tension
Handle Length ^[1]	35 in. (889.0 mm)

^[1] Weight Approximate, ^[2] Tong and Backup

RELIABLE. SAFE. EFFICIENT. TRUSTED.

sales@eckel.com | www.eckel.com